BioKnox

eSSL®

GEO BiO 30

GEO Based Fingerprint Time & Attendance With Access Control System

Fingerprint   RFID   Access

Specification

User Capacity: 2,000

Fingerprints Capacity: 2,000

Card Capacity: 2,000

Transaction Storage: 1,00,000

Push Data: Yes

Card Reader: Yes

Fingerprint sensor: 500 DPI Optical Sensor

FAR : <=0.0001% / FRR : <=1%

Identication Speed: <= 1sec

Algorithm Ver: 10

Display: 2.8" TFT Sceen

Keypad: 4 x 4 Keypad

LED Indicator: Green/Red

Schedule Bell/Speaker: Mini Speaker

Communication: TCP/IP, USB-host, WiFi

Standard Features: Inbuilt Battery Backup,

Self Service Query, DST, T9 Input

Power Supply: 12V DC, 1.5 Amps

Operating Temprature: 0°C to 45°C

Operating Humidity: 20% - 80%

Dimension (in mm): 185 x 140 x 30

Access Control: Yes

Relay: 12V

Exit Readers: No

Exit : No Touch & Push Button

Inbuilt Battery: yes

Compatible Software & SDK

- Bioknox desktop, Web & Cloud

Major Applications

- Time & Attendance , Canteen management,
  School attedance, Production Management,
  Gym & clubs

Disclaimer: Brief specifications are mentioned here.Specifications may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development