



Access Control Terminal

MA500



Specification

Users: 3000 Fingerprints
Card Capacity: 30,000
Transaction: 1,00,000 Logs
Sensor: Optical Sensor with protective cover
Algorithm Version: Finger V10.0
Optional proximity or mifare card reader
Communication: TCP/IP, RS485
Access Control Interface: Electric lock,
Door sensor, Alarm, Exit button
Wiegand Signal: Wiegand out
Power Supply: 12V DC, 3A
Operating Temperature: 0°C - 45°C
Operating Humidity: 20% - 80%
Dimension(WxHxD): 83 x 127.5 x 74 mm
Ingress Protection Rate: IP65

Features :

- ▶ Vandal resistant & IP65 waterproof, ideal for outdoor installation
- ▶ Combine master and slave system to secure the entrance and exit with dual biometric authentication simply and easily by RS485
- ▶ Support Anti-passback to maximize security level
- ▶ Configurable wiegand output to connect with most of the access control panel brands, easy replacement into existing systems
- ▶ Various types of alarm such as tamper alarm, door sensor alarm, duress alarm etc.

Disclaimer: Brief specifications are mentioned here. Specifications may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development