



## Flap Barrier

**FB-TL-219**

### Specification

Passage width (Max) :  $\leq 500$ mm  
Throughput rate : 35 P/M  
Power Supply : 100V ~ 240V AC  
Operational Voltage : 24V DC  
Max Power Consumption : 30W  
Frequency : 50Hz ~ 60Hz  
Protection Level (IP) :  $\geq 44$   
Working Temperature :  $-25^{\circ} \sim +70^{\circ}$   
Electro-magnetic Drive : DC  
Dimension excluding bars : 800 X 280 X 960 mm  
Weight : FB-TL-119-L/R : 40kg

### Feature :

- Use IC cards, ID cards, bar code or magnetic cards as automatic identification system.
- Display has been in use for statistics and numbers
- With voice and strobe light alerts
- A combination of infrared sensors and police anti-illegal entry into pedestrian access.
- Double anti-clipping function, photocell anti-clipping and mechanical anti-clipping
- The barrier can be set to delay closing in 1 ~ 60s after a valid card reading
- Single passage in the set direction
- Bi-directional single passage
- Plastic toughened glass
- Always free or locke

Disclaimer: Brief specifications are mentioned here. Specifications may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development