



## Multi-Biometric Time Attendance & Access Control System

### SilkBio-101TC



## Specification

### Storage Capacity

Face Capacity : 2,000  
Fingerprint Capacity : 3,000  
ID Card Capacity : 3,000  
Transaction Capacity : 1,00,000

### Communication

TCP/IP, USB-Host, Wi-Fi(Optional)  
Push Data : Yes

### Standard Functions

Work Code, SMS, DST, Scheduled-bell, Self-Service Query, Automatic Status Switch Photo ID, T9 Input, Camera, 9 digit user ID, Built-in Battery, Multiple Verify Mode, External Bell  
Access Control Interface : Lock, Door Sensor, Exit Button, Alarm

### Optional

Optional Functions : Mifare

### Visual

Display : 2.8-inch TFT Screen

### Power & Environment

Operating Temperature : 0°C ~ 45°C  
Power Supply : DC 12V --- 1.5A  
Operating Humidity : 20% - 80%  
Dimensions (in mm) : (L)180 x (W)154 x (H)34.2

### Features

- Multi-biometric fast verification
- Touch Keypad
- Infrared auto-turning on function to save power
- Quick recognition of dry, wet and rough fingers
- Multi-language supported
- Built-in 2000mAh backup battery to extend operation time
- Prevents duplicated face registration and supports fake face detection function

Disclaimer: Brief specifications are mentioned here. Specifications may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development